The calibration sheet attached is the original calibration sheet for your REF TEK product and includes contact information and branding for the company that performed the testing.

Reftek Systems Inc. purchased the REF TEK product line in May 2020.

Reftek Systems will honour existing product warranties and extended warranties.

ANY QUESTIONS OR REQUESTS FOR SUPPORT SHOULD BE ADDRESSED AS FOLLOWS:

Sales & Administrative: sales@reftek.com

Support & Engineering: support@reftek.com

Accounting: accounting@reftek.com

Address: 36 Topple Drive, Dartmouth, NS Canada B3B 1L6

Phone: +1-902-444-7650

Fax: +1-902-444-7651

Trimble Inc.
5217 Tennyson Parkway
Suite 400
Plano, TX 75024
Support Phone: 1-888-879-2207
Support Email: MonSol_Support@trimble.com
www.trimble.com/monitoring

REF TEK 147A-01/3/INT/SM
S/N: 16054

Normalized Magnitude-frequency Characteristics

Freq.(Hz)	Z-Axis (Vertical)	Y-Axis (North/South)	X-Axis (East/West)
1.00	1.0024	1.0047	1.0025
10.00	1.0000	1.0000	1.0000
20.00	0.9933	0.9889	0.9931
30.00	0.9838	0.9767	0.9833
40.00	0.9737	0.9663	0.9728
50.00	0.9653	0.9592	0.9639
60.00	0.9604	0.9559	0.9583
70.00	0.9611	0.9572	0.9579
80.00	0.9691	0.9646	0.9643
90.00	0.9846	0.9781	0.9779
100.00	1.0088	0.9989	0.9996
120.00	1.0826	1.0653	1.0674
140.00	1.1569	1.1471	1.1434
160.00	1.1226	1.1454	1.1330

Sensitivities

	Z-Axis (Vertical)	Y-Axis (North/South)	X-Axis (East/West)
Output Sensitivity (V/g)	2.500	2.501	2.501
Cross-axis Coupling (g/g)	0.08%	0.12%	0.52%