

131D-BH

TRIAxIAL ACCELEROMETER

The 131D-BH is a 3-axis $\pm 4g$ full scale accelerometer with a noise performance of $1.2 \mu g/\text{rtHz}$. The accelerometer outputs an industry standard $\pm 10V$ full scale output. The 131D-BH is best suited for structural engineering applications (bridge and dam monitoring) when the project requires accelerometers to be deployed in triaxial configuration. The Reftek 131D-BH housing is made of Stainless Steel and is sealed to meet IP68 standards for watertight integrity.

Reftek model 131D Accelerometers provide excellent dynamic range and low noise performance useful when paired with digitizers like the Reftek Wrangler. These accelerometers use a Micro-Electro-Mechanical System (MEMS) variable capacitance displacement sensor. The accelerometer is inherently stable over temperature, with excellent reliability, exceptional linearity over a broad dynamic range, excellent bias stability, and little hysteresis errors or offset drift problems that are usually associated with other accelerometer designs. The model 131D-BH is suitable for borehole sizes between 3-3.5 inches.

KEY FEATURES

- » Low Noise.
- » State-of-the-Art MEMS Capacitive Accelerometer
- » Sensitivity & Offset stable over wide temperature range

APPLICATIONS

- » Structural Monitoring

MODEL	131D
ELECTRICAL	
Full-scale Range	$\pm 4g$
Full-scale Output	$\pm 10V$
Sensitivity	$2.5V/g$
PERFORMANCE - MEMS CAPACITIVE ACCELEROMETER	
Self-Noise	$1.2 \mu g/\text{rtHz}$
Dynamic Range	118 db (DC -10 Hz) @ 200sps
Linearity	$\pm 1\%$ of full scale
Frequency Response	DC - 600 Hz (± 3 dB)
Self-test Response	Logic level input will produce 0.5g positive output
Lightning Protection	Built-in surge protection
Cross Axis Sensitivity	$<0.0005g/g$
Thermal Drift	$<0.5mg/^\circ C$
Natural Frequency	1300 Hz
POWER	
Supply Voltage	9-18 VDC
Supply Current	$\sim 200mA$
ENVIRONMENTAL	
Operating Temperature	$-4^\circ F$ to $167^\circ F$ ($-20^\circ C$ to $75^\circ C$)
Storage Temperature	$-40^\circ F$ to $185^\circ F$ ($-40^\circ C$ to $85^\circ C$)
Humidity	0 – 100% non-condensing
MECHANICAL - 131D-BH	
Dimensions	2.3" dia x 36" long
Weight	16.5 lbs (~ 7.5 kg)
Depth	100 meters

CUSTOMER SUPPORT

REF TEK products are installed in locations around the world, from urban settings to rainforests to deserts. The environments are often challenging for electronics and REF TEK Systems is committed to providing reliable, practical support. Our team includes seismologists and seismic installation experts as well as engineers and technicians.

Contact support@reftek.com.